

AREVENCA
COMPLEJO AREVENCA
ARMADORES Y ASTILLEROS VENEZOLANOS C. A
EMPRESA VENEZOLANA DE INDUSTRIAL NAVALES
PUERTO SAN FRANCISCO JAVIER
TERMINAL DE AGUAS PROFUNDAS DE ORIENTE
ZONA DE ACTIVIDADES LOGÍSTICAS DE ORIENTE

Gasoil d2

NAME QUANTITIES

Cetane index not less than 45

Diesel index not less than 53

Distillation:

I.P.P., °C, not more than 162

50% °C, not more than 280

96% °C, not more than 360

Viscosity at 20°C, mm² sec 3.6-6.0

Pour point °C, not more than -10

Cloud point °C, not more than -5

Flash point, °C (closed cup), not less than 62

Sulphur, %, not more than 0.2

Mercaptane sulphur, %, not more than 0.02

HS content absent

Test with copper plate positive

Alkali absent

Colour ASTM, not more than 2.0

Acidity, mg KON/loog gasoil, not more than 10

Lodine number, g iodine/loog gasoil, not more than 6

Oxyd Ashes, not more than 0.01

Conradson carbon residue, 10th % not more than 0.20

Filtering coefficient, not more than 3

Sediments, % absent

Water content absent

Density at 20°C, kg/M³, not more than 860

Density at 20°C, kg/M³, not less than 830