


AREVENCA
COMPLEJO AREVENCA
ARMADORES Y ASTILLEROS VENEZOLANOS C. A
EMPRESA VENEZOLANA DE INDUSTRIAL NAVALES
PUERTO SAN FRANCISCO JAVIER
TERMINAL DE AGUAS PROFUNDAS DE ORIENTE
ZONA DE ACTIVIDADES LOGÍSTICAS DE ORIENTE



Specifications:

SPECIFICATIONS OF GASOIL D2

NAME QUANTITIES

Cetane index not less than 45

Diesel index not less than 53

Distillation:

I.P.P., °C, not more than 162

50% °C, not more than 280

96% °C, not more than 360

Viscosity at 20°C, mm² sec 3.6-6.0

Pour point °C, not more than -10

Cloud point °C, not more than -5

Flash point, °C (closed cup), not less than 62

Sulphur, %, not more than 0.2

Mercaptane sulphur, %, not more than 0.02

HS content absent

Test with copper plate positive

Alkali absent

Colour ASTM, not more than 2.0

Acidity, mg KON/loog gasoil, not more than 10

Iodine number, g iodine/loog gasoil, not more than 6

Oxyd Ashes, not more than 0.01

Conradson carbon residue, 10th % not more than 0.20

Filtering coefficient, not more than 3

Sediments, % absent

Water content absent

Density at 20°C, kg/M³, not more than 860

Density at 20°C, kg/M³, not less than 830